



CDH-62L

CPR 系列

平板式螺纹搓丝机/CPR Series Flat Die Thread Roller

CPR系列 平板式螺纹搓丝机

CPR Series Flat Die Thread Roller



CPR-20L

机器型号 M/C Type 機械型番	单位 Unit	CPR-3	CPR-6S	CPR-8L	CPR-10L	CPR-12S	CPR-12L	CPR-16S	CPR-16L	CPR-20S	CPR-20L	CPR-25LL	CPR-30L	CPR-42L
最大搓丝螺纹直径 Thread dia. Range 最大ネジ製造径	mm	2~3	3~6	4~8	4~10	8~12.7	8~12.7	10~16	10~16	10~20	10~20	12~25.4	20~31.75	20~42
自攻螺丝搓丝螺纹直径 Tapping Screw Thread dia. Range 最大ネジ製造径	mm	#2~#4	#4~#10	#6~#14	#6~#14	—	—	—	—	—	—	—	—	—
搓丝螺纹长度 Thread Length Range ネジ製造長さ	mm	3~22	8~50	12~50	(M10x70) 14~102	20~75	20~75	20~100	20~100	30~100	30~100	30~250	30~150	40~160
螺丝最大头下长度 Shank Length Range Under Head 最大ネジ製造長さ	mm	3~22	8~50	12~100	14~102	20~100	20~300	20~150	20~300	30~150	30~300	30~350	30~300	30~300
最高生产速度 Max. Output Speed 最高速度	pcs/min	320	240	154	152	120	60	104	60	72	56	50	47	40
固定/活动搓丝板尺寸(长x宽x高) Rolling die Dimensions Stationary/moving (LxTxW) 製造ダイス寸法(固定/移動高さx長さx高さ)	mm	58/66x20x25	90/105x25x54	110/130x25x55	180/200x35x110	200/230x38x85	200/230x38x85	230/260x40x105	230/260x40x105	280/310x50x105	280/310x50x105	400/450x65x255	500/550x65x155	700/750x65x165
电机功率 Motor Power モーターパワー	kW	1.5	5.5	7.5	15	18.5	15	18.5	18.5	30	30	45	55	90
机器大约重量 Approx. Weight 機械重量	kgs	550	1,800	2,800	3,800	4,800	5,000	6,000	6,000	7,000	7,000	20,000	23,000	34,000
机器大约外形尺寸(长x宽x高) Area Space (LxWxH) 機械外形寸法(長さx幅x高さ)	mm	1,520x800x1,210	2,240x990x1,440	2,410x1,080x1,440	2,950x1,100x1,560	2,360x1,000x1,540	3,100x1,450x1,800	2,750x1,530x1,800	2,750x1,530x1,800	2,840x1,590x1,910	2,840x1,590x1,910	3,510x1,990x2,420	5,280x2,180x2,910	6,750x2,400x3,000
阶梯式毛坯送料器外形尺寸 Up-pushing Type Blank Feeder Dimension (LxWxH) 階段式半製品送り機構外形寸法	mm	—	—	—	—	1,250x950x1,800	1,250x950x1,800	1,270x920x2,070	1,570x920x2,070	1,270x920x2,070	1,570x920x2,070	1,500x1,540x2,500	1,500x1,540x2,500	1,500x1,540x2,500

备注:

- 本公司保有规格修改之权利,规格修改时不另行通知。
- 生产速度随产品形状、材质及热处理硬度而有所差异。

REMARKS:

- Modification is subjected to change without any notice.
- Production speed will differ depending upon product's shape and material.